SILICA: Certified Counterfactual Evaluation of Identifiability in Unseen-Language Induction

Pengcheng Xu
University of California, Irvine

Xinyu Guan
Alibaba Inc.

Abstract

Knowing an answer is not the same as knowing that the evidence determines it: several unseen lexicons or grammars can fit every clue in a prompt yet disagree on a query. We introduce SILICA, a shortcut-audited benchmark of certified identifiability. Every record publishes an executable Boolean program over a finite lexicon–grammar class, and exhaustive filtering proves consensus or disagreement between compatible witnesses. Its 12,288 records span 192 packed templates; each of 6,144 program/evidence states is queried two complementary ways with opposite correct actions, at constant class size (128) and posterior size (16). Frozen shortcut controls and learned probes score exactly 50%, and a solver reading only the prompt reproduces all 12,288 gold labels. Of eight sealed silent single-pass panel conditions up to 32B, the four passing the format gate (all Qwen2.5) answer almost independently of gold answerability with payloads near chance, and no condition completes any of the 192 eight-row route groups. A 235B model permitted a visible reasoning trace escapes that regime, reaching .671 balanced strict joint accuracy and 11/192 complete groups, while the same checkpoint without the trace stays at $-.005$ signal and 0/192: size alone does not move the endpoints, and 94% of groups stay unsolved.

1 Introduction

Suppose two lexicons explain every translation in a prompt. Under one, *v0* means SEE; under the other, it means HELP. If the query asks for *v0*, producing either translation selects an arbitrary world not licensed by the evidence. The scientifically correct output is not a lower-confidence guess: it is the claim that the answer is *underdetermined*. Once a discriminating clue arrives, the same query can become answerable.

Accepted to Findings of the Association for Computational Linguistics: EACL 2027.

Large language models are increasingly asked to infer rules, tool semantics, schemas, and unfamiliar languages from context. In each setting, a model that can solve identifiable cases but cannot recognize non-identifiability will confidently complete missing conventions. Conversely, indiscriminate refusal can look accurate whenever unanswerable examples dominate. We therefore ask a narrow question: **can a model distinguish what follows uniquely from the supplied evidence from what remains one of several compatible choices, and then execute the unique answer?**

This capability differs from calibrated confidence. Confidence concerns a model's probability of correctness; identifiability is a property of an evidence set, query, and declared hypothesis class. It also differs from ordinary unanswerable question answering: SILICA constructs a checkable reason for non-answerability and can make the label change under a controlled change to evidence values. Figure 1 gives the central example.

Under a silent single-pass protocol, on a sealed eight-condition panel, the answer is no, and in one specific way: each condition answers at a rate essentially unrelated to whether the evidence determines an answer ($|\mathrm{AR} - \mathrm{FCR}| \leq .017$), so scale slides it from "always answer" to "almost always abstain" without completing one of the 192 route groups. Permitting a visible reasoning trace on a much larger reasoning model breaks that regime without solving the task, while the same permission does not help a small reasoning model and a visible scratchpad does not help two panel models: the benchmark is a gradient rather than a floor.

We make five contributions:

1. We formalize answerability as consensus over an explicitly declared finite lexicon–grammar version space and provide independently reconstructible consensus or disagreement certificates.




Figure 1: **One state, two opposite correct actions.** A renderer-faithful excerpt of one immutable released query pair; Appendix B.1 prints both complete two-message inputs and their prompt hashes. The hypothesis declaration and projected observations are byte-identical; the renderer necessarily changes the structured query, `response_task`, and task-conditioned response schema. Panel 2 replays the elimination one public filter at a time, $256 \to 128 \to 64 \to 32 \to 16$: the program $C(\varphi)$ halves the assignments, then the three dictionary facts pin $M{=}0$, $V{=}0$ and $D{=}1$, leaving the same 16 survivors for both queries; every ratio shown is measured from the replayed counts. Each square is one survivor in sealed certificate order, and the two branches recolour that same set: all 16 map `helu` to FOX, whereas `order_family` splits 8/8 with witnesses `h002` and `h018`, yielding the strict JSON actions `ANSWER` and `ABSTAIN`. The survivors are recomputed from the public record and reproduce the sealed version-space hash; support counts, witnesses, and gold objects are evaluator-only.

2. We construct posterior-matched, same-state complementary query pairs: the declaration and projected observations are unchanged, while the structured query, response task, and task-conditioned schema differ; one query must be answered and the other abstained from.

3. We separate scored rows from semantic scale through deterministic distance-gated packing, 192 primary template clusters, an independent clean-room implementation, and exact plus learned shortcut gates.

4. We freeze before output inspection a provenance-sealed direct-model panel and strict paired endpoints that separate decision orientation, exact payload execution, complete-group success, response validity, and false certainty, and we show that under a silent single-pass protocol the panel collapses onto two constant policies: answering carries almost no information about answerability, payloads stay near the exact within-unit chance level, and the complete-group endpoint is zero for every condition.

5. We isolate the protocol's confounds with matched controls: a visible reasoning trace lifts a 235B reasoning model off the constant-policy frontier but not a 1.7B one, decoding is not the cause, and scratchpads, prompt stripping and a stated shortcut rule leave two panel models at chance, although the gold decision needs at most four Boolean operations on three printed bits.

We deliberately do not claim broad natural-language validity, human-like acquisition, or a scaling law. The finite micro-language setting trades ecological coverage for a capability label that can be proved exactly. We release the benchmark, its generator and validators, the evaluator, and every model response analyzed here.[1]

[1]Code: a public code repository (link to follow); data and model responses: a public Hugging Face dataset (link to follow).

2 Positioning and Related Work

Human-authored linguistic puzzles test induction from few examples (Şahin et al., 2020; Chi et al., 2024; Bean et al., 2024; Sánchez et al., 2025), while grammar-book and in-context translation evaluate learning from richer resources (Tanzer et al., 2024; Aycock et al., 2025; Zhang et al., 2024; Marmonier et al., 2025). Controlled languages and formal tasks make compositional generalization measurable (Lake and Baroni, 2018; Ruis et al., 2020; Kim and Linzen, 2020; Valvoda et al., 2022), and synthetic impossible languages probe what language models can learn (Kallini et al., 2024). FOLIO pairs natural-language reasoning with machine-verified first-order-logic annotations (Han et al., 2024), whereas InductionBench tests recovery of latent subregular functions (Hua et al., 2025). SILICA complements these resources: its target is neither translation quality, unrestricted deduction, nor recovery of one intended hidden rule, but the meta-decision of whether *every declared rule still compatible with the observations* entails the same query answer.

AmbiEnt and DUST directly study linguistic ambiguity and semantic underspecification, respectively (Liu et al., 2023; Wildenburg et al., 2024); AbstentionBench evaluates abstention across twenty datasets spanning unknown answers, underspecification, false premises, subjective interpretations and outdated information (Kirichenko et al., 2025); and selective classification formalizes prediction with a reject option. In the noise-free setting its consistent selective strategy abstains exactly where the version space disagrees (El-Yaniv and Wiener, 2010), which is the decision rule SILICA certifies. SILICA's distinctive supervision is therefore not the rule but an exhaustive certificate over a declared, in-prompt finite class, plus matched changes in evidence values. This makes non-answerability causal within the declared construction rather than an annotator judgment or a property inferred from a single reference.

Appendix H maps which of these design features each neighbouring resource states as primary, and which SILICA adds. Benchmark artifacts can support unexpectedly strong shortcuts (Gururangan et al., 2018), and a failing partial-input baseline does not certify their absence (Feng et al., 2019). The released construction is therefore the third, after two candidate designs were rejected by explicit shortcut audits. Its same-state complementary queries are contrast-set-like local interventions (Gardner et al., 2020), but the opposite labels follow from exhaustive semantics rather than annotation. Query-masked exact controls and word/character probes under held-out-template and held-out-family splits test whether the intervention survives beyond identity matching. Calibration methods correct biased output probabilities (Zhao et al., 2021) or align confidence with correctness (Jiang et al., 2021); our gold answerability is instead an exactly computed property of the declared finite problem, with false certainty reported as a behavioral consequence.

3 Certified Identifiability

3.1 Executable languages and version spaces

Let $z \in \mathcal{Z}$ be a typed event meaning and let a language hypothesis $h = (\ell, g)$ pair a part-of-speech-preserving lexicon with an executable grammar. Its deterministic realizer $R_h : \mathcal{Z} \to \Sigma^*$ maps meanings to synthetic strings. Meanings are sampled before realization, so the unknown utterance and canonical task answer are two views of one structure rather than a word substitution.

An episode publishes a finite class $\mathcal{H}_e$ but hides the sampled true member. Dictionary observations and parallel meaning–surface pairs form evidence E. Exact filtering yields the version space (Mitchell, 1982)

$$\mathcal{V}_e(E) = \{h \in \mathcal{H}_e : h \models E\}, \tag{1}$$

where $h \models E$ means that h satisfies every observation in E. For task t and query q, define the supported canonical answers

$$A_t(q, E) = \{f_t(h, q) : h \in \mathcal{V}_e(E)\}. \tag{2}$$

Gold is `ANSWER` with the unique member of A_t when $|A_t| = 1$ and `ABSTAIN` otherwise. The certificate stores canonical hashes of the survivor and answer-support sets. An underdetermined item additionally stores two surviving hypotheses with different answers; an answerable item is rechecked for unanimity. None of these fields is model-visible.

Proposition 1 (Evidence-relative necessity)**.** *If* $|A_t(q, E)| > 1$*, no learner observing only* $(\mathcal{H}_e, E, q)$ *can guarantee the correct task answer for every possible true language in* $\mathcal{V}_e(E)$*.*

The proof is immediate from two observationally indistinguishable witnesses with different task answers and is given in Appendix A. The claim

is deliberately relative to $\mathcal{H}_e$; it is not uniqueness among all conceivable human languages.

3.2 Adversarial construction history

We treat shortcut discovery as part of benchmark construction. In the initial factorial control, a train-fit budget–query rule that ignored evidence values reached 93.05% balanced decision accuracy. A first revision removed that route but leaked every label through public posterior cardinality. Both designs are retained as falsified development history, not benchmark evidence. The released construction was accepted only after constant-cardinality, paired-query, learned-probe, and independent clean-room gates were fixed before direct-model inference.

3.3 Posterior-matched guarded switches

The base language inventory has eight binary lexical and grammatical features, so $\mathcal{H}_0 = \{h_b : b \in \{0,1\}^8\}$ contains 256 executable languages. For semantic template ϕ, the item publishes a canonical Boolean program C_ϕ and declares

$$\mathcal{H}_\phi = \{h_b \in \mathcal{H}_0 : C_\phi(b) = 1\}. \tag{3}$$

Every released program admits exactly 128 languages. Three dictionary facts reveal a selected feature triple X; exact filtering leaves 16 candidates for every evidence state.

The program implements a guarded switch between two query-facing coordinates. Conditioned on any released X, exactly one coordinate is constant over all 16 survivors while the other retains both values. We therefore ask two queries of the same program/evidence state. Their hypothesis declaration and projected observations are identical. In the rendered input, the structured query, response task, and task-conditioned canonical response schema change: one requires `ANSWER` with the unanimous payload, and the other requires `ABSTAIN` with two explicit evaluator-only witnesses.

A worked instance. Take the released parity item of Figure 1. Its published program is $g = (M \oplus D \oplus V) \wedge (M{=}V)$, with $g \Rightarrow \texttt{noun_swap}_{01} = \mathrm{ITE}(D, V, M)$ and $\neg g \Rightarrow \texttt{order_family} = \mathrm{ITE}(V, D, \neg M)$, where M, V, D abbreviate three of the eight binary features. Of the $2^8 = 256$ base languages, exactly 128 satisfy the program. The three dictionary facts `pudo`→RED, `levu`→SEE and `reze`→DOG pin $M{=}0$, $V{=}0$ and $D{=}1$, leaving 16 survivors. All 16 map `helu` to FOX, so the lexical query is answerable; the same 16 split 8/8 between subject-initial and verb-initial order, so the grammar query is not. Nothing in this derivation is withheld: the program, the three facts, the realization rules and the decision rule are all in the prompt, and Figure 5 in Appendix K walks the whole elimination step by step. Only the survivor set, its support partition and the two disagreeing witnesses are evaluator-only.

A paired route contains four evidence states crossed with the two query roles. The states balance active/inactive guards and both payload values, so each four-row orientation is a complete 2×2 decision–payload unit and the linked eight rows contain four examples of each action. The public release uses lexical and grammar-feature queries with exact canonical answers. Four families encode the guarded-switch principle as parity guards (implications), majority guards (disjunctions), equality chains, and selector multiplexers (if–then–else); they are structurally different encodings, not four claims of unrelated linguistic mechanisms.

3.4 Semantic packing, routes, and separation

Scale comes from distinct behavior, not renamed formulas. Candidate enumeration yields 2,644 family-specific programs (2,411 globally unique paired behaviors). We compare programs by a length-16 ternary outcome signature: one position for each query role at each of eight X states, taking values `ABSTAIN`, `ANSWER:0`, or `ANSWER:1`. Candidates must be at Hamming distance at least four positions from every fixed support template and every selected evaluation template, both under this paired signature and the derived full-class truth table.

The deterministic search checks all 24 family orders under two static conflict scores. The best balanced packing found across the 48 frozen configurations has 57 templates per family. We select 48 (192 total), leaving measured headroom rather than adding nuisance variants. Twelve support templates are semantically disjoint from evaluation, with the selector family held out entirely from support. Eight lexical–grammar routes per evaluation template cover every public X state and each query axis twice. Ordered placeholder roles, target languages, survivors, and certificates remain evaluator-only.

4 Evaluation

4.1 Prevalence-robust selective metrics

Let $G \in \{A, U\}$ be the gold action and $\widehat{G}$ the predicted action. Answerable decision recall (AR) and underdetermined abstention recall (UR) are

$$\mathrm{AR} = P(\widehat{G} = A \mid G = A), \tag{4}$$

$$\mathrm{UR} = P(\widehat{G} = U \mid G = U). \tag{5}$$

Their unweighted mean, balanced decision accuracy $\mathrm{BDA} = (\mathrm{AR} + \mathrm{UR})/2$, prevents a policy or budget's label prevalence from dominating the score. Exact answerable recall (EAR) replaces the first event with `ANSWER` plus the canonical payload; balanced joint accuracy is $\mathrm{BJA} = (\mathrm{EAR} + \mathrm{UR})/2$. We also report micro-averaged strict joint accuracy, answer coverage, invalid response rate, and false certainty

$$\mathrm{FCR} = P(\widehat{G} = A \mid G = U). \tag{6}$$

Two derived quantities separate policy from capability, because AR, UR and EAR each confound them. The *decision signal* $\mathrm{AR} - \mathrm{FCR}$ is zero exactly when a predictor's `ANSWER` rate does not depend on the gold action, whatever that rate is; on format-valid rows $\mathrm{BDA} = \frac{1}{2} + \frac{1}{2}(\mathrm{AR} - \mathrm{FCR})$, so a vanishing decision signal forces chance-level balanced decision accuracy. *Conditional payload accuracy* $\mathrm{CPA} = \mathrm{EAR}/\mathrm{AR}$ measures exact payload execution among answerable rows the model actually chose to answer, and is left undefined rather than imputed when $\mathrm{AR} = 0$. Its evidence-blind reference is exactly $1/2$: within every four-cell unit the two answerable rows carry different canonical payloads, so a payload chosen without reading the evidence values is correct on exactly one of them. Metrics are undefined rather than imputed when a stratum lacks either gold class. Budgets and tasks remain separate in primary tables.

Paired endpoints prevent a globally inverted predictor from looking competent. A four-row orientation succeeds only if its entire gold decision pattern is correct; strict success additionally requires both answerable payloads. The linked all-eight endpoint requires both orientations and all four same-state query complements to be correct. We also report unoriented complement and factorial consistency, but label them structural diagnostics rather than accuracy because inversion can satisfy them.

4.2 Strict direct-model protocol

Direct models see the response task, Boolean DSL semantics, canonical public program, feature-value axes, realization rules, three observations, query, decision rule, and exact response schema. The instruction is explicit, not open-ended: the system message names the exact procedure and the declaration repeats the universe and filter. No worked example is given and the model is told to reason silently, so the panel measures single-pass execution of a stated algorithm, not discovery of one. They never see family, route, template or pairing metadata, observation IDs, semantic hashes, structural statistics, survivors, witnesses, or gold fields. The response must be one whole JSON object with exactly `decision` and `answer`: `ANSWER` couples to a canonical non-null payload and `ABSTAIN` couples to JSON null.

Each condition in the frozen original local panel runs Hugging Face Transformers (Wolf et al., 2020) on one GPU with bfloat16, batch size two, greedy decoding, temperature and seed zero, at most 384 new tokens, the tokenizer chat template, and no response repair. A generation that does not terminate with EOS is invalid. Any tensor-parallel extension is a separately frozen condition. Hosted inference is a separate stratum with provider pinning, disabled fallbacks, JSON mode, and an independently archived request identity. Schema violations and hosted request failures count as wrong; local operational faults abort the archive rather than fabricating model outputs.

Every run binds the dataset release, public cohort, post-selection gold audit, model and tokenizer revisions, complete weight/tokenizer file inventory, effective generation configuration, prompt and request hashes, source commit, executed source-file hashes, runtime libraries, GPU, token IDs, and one UUID. The evaluator reparses raw text and recomputes these identities. Source, cache, weight, or configuration drift invalidates the run rather than creating a new unlabeled condition.

4.3 Frozen panel and controls

The common cohort contains 1,536 rows: one complete eight-row route for each of 192 templates. The pre-output-frozen local panel spans Qwen2.5 at 0.5B, 1.5B, 3B, 7B, 14B, and 32B (Yang et al., 2024); Phi-3.5-mini (Abdin et al., 2024); and SmolLM2-1.7B (Ben Allal et al., 2025), all at immutable revisions. Qwen2.5-14B is addi-

tionally evaluated on all 12,288 rows; Qwen2.5-32B is the stronger common-cohort sentinel; and Qwen2.5-1.5B has a cross-hardware replicate that is an implementation check rather than another sample. Hosted free models are reported only if a complete provider-pinned 1,536-row archive is obtained; canaries and partial quota-limited runs never enter model comparisons.

Always-answer and always-abstain each attain 50% balanced decision accuracy. Exact generator and independent clean-room oracles must attain 100% strict joint accuracy, while every frozen query-masked exact control and query-visible learned probe must remain at 50%. These are construction gates, not competitors. A generic code agent may legitimately enumerate the class and reach the oracle ceiling; that condition measures executable access, not direct LLM reasoning or agentic planning.

5 Scale and Statistical Units

SILICA is a finite-registry benchmark with deliberately repeated views of each logical object. Its 12,288 scored records are organized as 1,536 paired route instantiations of 192 semantically packed templates; the row count is therefore coverage, not an iid sample-size claim. Table 1 makes every level and its statistical role explicit.

Figure 3 in Appendix C draws the same hierarchy together with the nuisance-balance gates and the sealed packing frontier. Each template contributes eight lexical–grammar query-axis routes. Each route contains four evidence states queried on both conditionally constrained coordinates, yielding opposite actions for every same-state pair. Across the full artifact this gives 1,536 unique full-class semantics, 1,536 unique paired query behaviors, and 3,072 query tasks. The common 1,536-row model cohort keeps one complete four-state route per template; only the full 12,288 rows cover all eight routes and all eight public X states for every template.

The registry is selected by deterministic distance-gated packing. Its minimum evaluation–evaluation and evaluation–support distance is four positions on a length-16 ternary paired-behavior signature. At $d = 4$, the balanced packing across 48 frozen greedy configurations contains 57 templates per family; selecting 48 leaves nine templates of measured headroom. Every row has declared class size 128 and posterior size 16, actions are exactly balanced, all frozen query-masked exact controls and query-visible learned probes score 50%, and all 12,288 rendered prompts have distinct verified hashes. An independent clean-room oracle agrees on 12,288/12,288 records.

Model intervals use 10,000 mechanism-family-stratified resamples of the 192 templates (48 per family). They are finite-registry cluster-sensitivity intervals, not iid population confidence intervals or null-hypothesis tests; exact numerators and denominators accompany percentages, and we do not interpret one–two point differences as model rankings.

6 Construction Audits and Model Evaluation

6.1 Correctness, balance, and shortcut resistance

Construction validity is established independently of any direct LLM-panel score. The in-generator oracle reproduces the decision, exact payload, posterior, and certificate on 12,288/12,288 rows. A standard-library clean-room program that imports no SILICA code independently reconstructs all 1,536 programs, 204 support-plus-evaluation placeholders, route choices, semantic identities, and distance gates; it also agrees on every row. Reversing row order leaves all ID-joined results unchanged, and same-seed regeneration is byte-identical.

The task is decidable from the prompt alone. Both oracles read dataset *records*, so neither answers the question a chance-level panel provokes: does the text the model receives suffice? We therefore added a solver that reads only the rendered user message, importing no oracle, certificate, or gold field. It re-derives the feature inventory, enumerates the declared 2^8 universe, applies the published program, filters by the three dictionary facts, and evaluates the query under every survivor. It reaches 12,288/12,288 exact strict joint accuracy, and the declared class size 128 and posterior size 16 reproduce from the prompt text on every row. Every scored item is therefore decidable from exactly what the model is given, so the panel's failures are failures of reasoning rather than of missing evidence.

The strongest query-masked control omits every query-side field while keeping the raw program and evidence, and is exactly at chance because every state receives both labels. Learned word and

Table 1: Exact SILICA hierarchy. Only the 192 semantic templates are primary generalization clusters; lower levels support paired and complete-unit endpoints.

Level	Count	Composition	Scientific role
Scored records	12,288	192×8 routes $\times 8$ rows	Repeated measurement views; never treated as iid examples
Complementary query pairs	6,144	Same program/evidence state, two queries	Query-conditioned identifiability contrast
Four-cell evaluator units	3,072	Two `ANSWER` and two `ABSTAIN` cells	Exact all-four endpoint
Paired route groups	1,536	Two linked four-cell units	Exact all-eight endpoint
Semantic-template clusters	192	Four mechanism families $\times 48$	Primary family-stratified resampling unit
Support templates	12	Fixed and semantically disjoint from evaluation	Packing/leakage gate; never scored

Table 2: Release gates. Shortcut values are exact held-out balanced decision accuracy; no direct LLM-panel output is used.

Gate	Audited result
In-generator exact oracle	12,288/12,288
Independent clean-room oracle	12,288/12,288
Prompt-only solver (rendered input)	12,288/12,288
Declared class size 128	12,288/12,288
Posterior size 16	12,288/12,288
Gold action balance	6,144/6,144
Same-state opposite-action pairs	6,144/6,144
Every frozen deterministic shortcut	6,144/12,288
Word/character, held-out template/family	6,144/12,288 each
Unique rendered prompt hashes	12,288/12,288
Minimum ternary-signature distance	4 of 16 positions

character TF-IDF logistic-regression classifiers (Pedregosa et al., 2011) remove IDs, hashes, route metadata and observed surface forms, then train under eight-fold held-out-template and four-fold held-out-family splits; all four meet the 0.500 gate exactly. These rule out the audited shortcut families, not every future heuristic.

6.2 Direct-model hardness is a measured claim

A shortcut-resistant construction is not automatically difficult for strong models. We therefore froze the model identities, common/full cohorts, generation envelope, endpoints, 10,000-replicate cluster-sensitivity procedure, and interpretation gates before inspecting any direct-model output. A usable run requires at least 99% request success and 95% strict format validity. We call the benchmark non-saturated only if Qwen2.5-14B, Qwen2.5-32B, and the cross-family Phi-3.5 configuration all have balanced strict joint accuracy below 90%, every upper sensitivity endpoint is below 95%, and the strongest usable model fails across multiple templates and mechanism families.

The decision carries almost no information about answerability. Figure 2 plots the panel; Table 9 in Appendix M prints it exactly. Across all eight conditions the signed gap $\mathrm{AR} - \mathrm{FCR}$ stays inside $[-.010, +.017]$ (Figure 2A). A policy answering at a fixed rate without consulting gold satisfies $\mathrm{AR} = \mathrm{FCR}$ identically, and $\mathrm{BDA} = \frac{1}{2} + \frac{1}{2}(\mathrm{AR} - \mathrm{FCR})$ on format-valid rows; the four format-valid conditions lie within .010 of that family, and no condition exceeds .503 balanced decision accuracy.

Payload execution stays near chance. All 3,072 four-cell units carry two *different* canonical payloads on their answerable rows, so an evidence-blind payload scores exactly $1/2$ per unit. Conditional payload accuracy spans .429–.522, and .497–.522 for the four format-valid conditions (Figure 2B).

Scale relocates the policy. Balanced strict joint accuracy rises from .249 at 3B and 7B to .495 at 32B, and the rise is entirely the abstention half: Qwen2.5-7B answers every row ($\mathrm{AR} = 1.000$, $\mathrm{UR} = .000$) while Qwen2.5-32B abstains on almost every row ($\mathrm{AR} = .030$, $\mathrm{UR} = .975$). Since always-`ABSTAIN` attains .500 and always-`ANSWER` with an evidence-blind payload attains .250, the four format-valid conditions lie between two constants, and the strongest interval $[.491, .499]$ falls *below* the always-`ABSTAIN` constant (Figure 2C).

Same-state pairs are unsolved. The endpoint the benchmark was built for asks for opposite, correct actions on the two queries of one state. On this same-state pair endpoint every panel condition except Qwen2.5-32B scores at or below the coin level $\alpha(1-\alpha)$ implied by its own answer rate α (32B: $23/768 = .030$ against .027), the all-eight endpoint is $0/192$ throughout, and Qwen2.5-14B completes the only four-cell patterns at all $(5/384)$, under the .061 expected from guessing.

A visible reasoning trace escapes the constant-policy regime. The panel above forbids a reasoning trace. We therefore ran one separately frozen




Figure 2: **Scale relocates the policy; it does not buy the capability.** (A) Every frozen condition lies within .017 of the AR = FCR diagonal, so its choice to answer is essentially independent of whether the evidence determines the answer. (B) Conditional on answering, exact payload accuracy stays near the within-unit chance level 1/2. (C) Across the four format-valid conditions, balanced strict joint accuracy climbs .249→.495 only by moving between the always-ANSWER (.250) and always-ABSTAIN (.500) constants, while the all-eight paired endpoint stays at 0/192 everywhere. (D) Per scored endpoint, the best value reached by *any* frozen condition, against the exact oracle at 1 (dashed). Response formatting is solved; the five endpoints that require using the evidence are almost entirely unclaimed. Taking a per-axis maximum flatters the panel, so the unclaimed area is unclaimed by every model at once. Intervals are 10,000-replicate family-stratified template-cluster resamples; exact numbers are in Appendix M.

Table 3: Matched controls on the 1,536-row common cohort, final JSON scored. Each pair changes one factor on a fixed checkpoint: the reasoning trace, the decoding, or (panel models) a visible <think> scratchpad with a 4,096-token budget. *Released prompt served through the ablation harness, which reproduces each sealed panel row to within .023. ⟨8⟩ counts complete eight-row route groups; Tok. is the mean number of generated tokens per row.

Model	Condition	Valid	AR−FCR	CPA	BJA	⟨8⟩	Tok.
Qwen3-235B-A22B	trace off	1.000	−.005	.489	.408	0/192	13
	trace on	1.000	+.431	.878	.671	11/192	5,427
Qwen3-1.7B	trace off	.987	−.001	.449	.224	0/192	19
	trace on	.950	+.029	.447	.279	0/192	3,868
Qwen3.5-2B	greedy	1.000	+.000	.487	.243	0/192	20
	stochastic	1.000	+.000	.435	.217	0/192	18
Qwen2.5-14B	silent*	.990	+.004	.503	.382	0/192	18
	scratchpad	.984	−.007	.496	.307	0/192	697
Qwen2.5-32B	silent*	1.000	+.003	.526	.495	0/192	14
	scratchpad	.961	+.009	.485	.264	0/192	832

extension condition that permits it: Qwen3-235B-A22B (Yang et al., 2025) in its GPTQ-Int4 release (Frantar et al., 2023), served by vLLM (Kwon et al., 2023) with tensor-parallel 4 and thinking enabled, a 16,384-token budget, a reasoning parser that separates the trace from the scored content, and scoring on the final content channel only. It returns a response on all 1,536 rows, with request success and strict format validity both 1.000, and it does not lie on the constant-policy frontier: decision signal .431 against $[-.010, +.017]$ for the whole panel, conditional payload accuracy .878 against a chance level of 1/2, balanced strict joint accuracy .671 [.645, .697] against a panel maximum of .495, same-state pair decision accuracy .518 (independent answering at its own rates would give .512), and 11/192 complete route groups where every panel condition scores 0/192.

The endpoints move, so they measure something achievable, and 181/192 route groups remain unsolved.

Neither size nor the trace alone moves the endpoints. That condition differs from the panel in three ways at once, so we ran matched controls (Appendix F). Holding the checkpoint and sampling fixed and disabling the trace, the same 235B returns to the frontier: decision signal −.005, conditional payload accuracy .489, and 0/192 complete route groups, at a mean 13 tokens per row against 5,427. Its stochastic sampling is thus not the cause, and on Qwen3.5-2B (Qwen Team, 2026) greedy and stochastic decoding give the same always-ANSWER policy (Table 3). Permission alone is also insufficient: Qwen3-1.7B (Yang et al., 2025) writes 3,868 tokens per row under the same budget yet reaches +.029 signal, payload accuracy .447 *below* the chance level of one half, and 0/192. At the small end, models often fail to *close* the trace at all: generation never terminates on 28.8% of rows for Qwen3.5-0.8B and 16.5% for Qwen3.5-2B, against 4.4% for Qwen3-1.7B and 0.0% for Qwen3-235B, with strict format validity 32.8%, 48.5%, 95.0%

and 100%. Non-termination falls with size within each family but not across them, so we read no scaling curve from four points.

Prompt interventions relocate the policy too. Four renderings served to Qwen2.5-14B and Qwen2.5-32B—released, a `<think>` scratchpad at 4,096 tokens, a user message 25.3% shorter on average, and the guarded-switch route in place of the enumeration—move AR from .085 to .730 (14B) and from .010 to .845 (32B), while the decision signal stays in $[-.007, +.013]$ and the all-eight endpoint at $0/192$ (Appendix J). The scratchpads write 697 and 832 tokens per row yet raise AR and FCR together. The gold decision itself is a Boolean function of the three revealed bits with minimal formula size at most four (Appendix I), so on the decision axis the collapse is not a shortage of the computation the task requires.

Prespecified verdict. Qwen2.5-14B and Qwen2.5-32B satisfy every frozen nonsaturation criterion: request success $\geq .99$, strict format validity $\geq .95$, balanced strict joint accuracy below .90, upper sensitivity endpoint below .95, and failures spanning all four mechanism families and all 192 templates. The prespecified full-artifact sentinel has since finalized with zero errors, and it reproduces every common-cohort finding at eight times the scale: over all 12,288 rows Qwen2.5-14B has decision signal $-.001$, conditional payload accuracy .502, balanced decision accuracy .495, balanced strict joint accuracy .379 $[.372, .385]$, and $0/1{,}536$ complete route groups. The third prespecified hardness model, Phi-3.5, yields no usable evidence: under our single-EOS protocol every response carries its end-of-turn token inside the scored span, typically after a JSON object and in 1,021 of 1,536 rows followed by a further turn. Stopping on its declared end-of-turn tokens removes that artifact, yet only $49/314$ rows are format-valid by the time limit (a complete run would stay below .83), as 60% loop to the token cap. The verdict therefore rests on its two Qwen2.5 legs; the third is unevaluable, not evidence of hardness. The cross-hardware Qwen2.5-1.5B replicate reproduces its primary-node counterpart to the last digit, an implementation check rather than an additional sample.

7 Discussion

What the benchmark isolates. SILICA makes "knowing when to answer" executable: retain every compatible explanation, answer only when their projections agree, then execute the payload. The silent panel fails at the first step, picking between the two decisions without consulting the property that determines the answer, so its decision axis degenerates to a constant policy whose only free parameter is how often to answer. This targets convention learning in schema induction, API discovery and rule following, where silently filling an unobserved convention fails.

8 Conclusion

Unseen-language induction should not reward arbitrary compatible worlds. SILICA makes the missing step executable: certificates define entailment, and posterior-matched queries test whether the query is used. Silent models trade one constant policy for another; among our conditions, only the 235B reasoning model with a visible trace escapes.

9 Limitations

SILICA is a closed synthetic instrument. It certifies identifiability only relative to each declared finite class, uses generated inventories and a simplified grammar, and its four mechanism families encode one guarded-switch principle, so it supports no claim about open-domain underspecification, tool discovery or natural low-resource translation. The constant-policy result concerns format-valid, direct, silent single-pass conditions: the format-valid evidence comes from one model family, a visible reasoning trace changes the result for at least one large reasoning model, and the trace-permitted conditions are exploratory controls rather than a scaling study. Format failures at small scale leave some conditions uninformative, the single-EOS protocol made one prespecified model unevaluable, the shortcut audits cover the families we specified, the prompt relies on two implicit naming conventions, and the intervals condition on one finite registry. Appendix N details each point.

10 Ethical Considerations

All forms and meanings are generated: there are no personal data, human-subject annotations, copyrighted corpus passages, or speaker-community claims. This lowers collection risk but supports

no ecological claim about real low-resource or endangered languages. Abstention is not automatically safe: error costs are context-dependent, and real translation requires community governance and qualified human review.

Generative-AI tools aided implementation, testing, literature discovery, and drafting, but not the authoritative meanings, surfaces, labels, or certificates, which the deterministic pipeline and validators produce. The authors remain responsible for all code, claims, citations, and prose.

References

Marah Abdin, Jyoti Aneja, Hany Awadalla, Ahmed Awadallah, Ammar Ahmad Awan, Nguyen Bach, Amit Bahree, Arash Bakhtiari, Jianmin Bao, Harkirat Behl, Alon Benhaim, Misha Bilenko, Johan Bjorck, Sébastien Bubeck, Martin Cai, Qin Cai, Vishrav Chaudhary, Dong Chen, Dongdong Chen, and 110 others. 2024. Phi-3 technical report: A highly capable language model locally on your phone. *arXiv preprint arXiv:2404.14219*.

Seth Aycock, David Stap, Di Wu, Christof Monz, and Khalil Sima'an. 2025. Can LLMs really learn to translate a low-resource language from one grammar book? In *International Conference on Learning Representations*, volume 2025, pages 12334–12357.

Andrew Bean, Simi Hellsten, Harry Mayne, Jabez Magomere, Ethan A. Chi, Ryan Chi, Scott A. Hale, and Hannah Rose Kirk. 2024. LINGOLY: A benchmark of olympiad-level linguistic reasoning puzzles in low resource and extinct languages. In *Advances in Neural Information Processing Systems*, volume 37, pages 26224–26237. Curran Associates, Inc.

Loubna Ben Allal, Anton Lozhkov, Elie Bakouch, Gabriel Martín Blázquez, Guilherme Penedo, Lewis Tunstall, Andrés Marafioti, Agustín Piqueres Lajarín, Hynek Kydlíček, Vaibhav Srivastav, Joshua Lochner, Caleb Fahlgren, Xuan-Son Nguyen, Ben Burtenshaw, Clémentine Fourrier, Haojun Zhao, Hugo Larcher, Mathieu Morlon, Cyril Zakka, and 3 others. 2025. SmolLM2: When smol goes big—data-centric training of a fully open small language model. In *Second Conference on Language Modeling (COLM)*.

Nathan A. Chi, Teodor Malchev, Riley Kong, Ryan A. Chi, Lucas Huang, Ethan A. Chi, R. Thomas McCoy, and Dragomir Radev. 2024. ModeLing: A novel dataset for testing linguistic reasoning in language models. In *Proceedings of the 6th Workshop on Research in Computational Linguistic Typology and Multilingual NLP*, pages 113–119.

Ran El-Yaniv and Yair Wiener. 2010. On the foundations of noise-free selective classification. *Journal of Machine Learning Research*, 11(53):1605–1641.

Shi Feng, Eric Wallace, and Jordan Boyd-Graber. 2019. Misleading failures of partial-input baselines. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 5533–5538.

Elias Frantar, Saleh Ashkboos, Torsten Hoefler, and Dan Alistarh. 2023. OPTQ: Accurate quantization for generative pre-trained transformers. In *The Eleventh International Conference on Learning Representations*. Preprint version titled "GPTQ: Accurate Post-Training Quantization for Generative Pre-trained Transformers", arXiv:2210.17323.

Jerome H. Friedman. 2001. Greedy function approximation: A gradient boosting machine. *The Annals of Statistics*, 29(5):1189–1232.

Matt Gardner, Yoav Artzi, Victoria Basmov, Jonathan Berant, Ben Bogin, Sihao Chen, Pradeep Dasigi, Dheeru Dua, Yanai Elazar, Ananth Gottumukkala, Nitish Gupta, Hannaneh Hajishirzi, Gabriel Ilharco, Daniel Khashabi, Kevin Lin, Jiangming Liu, Nelson F. Liu, Phoebe Mulcaire, Qiang Ning, and 7 others. 2020. Evaluating models' local decision boundaries via contrast sets. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 1307–1323. Association for Computational Linguistics.

Suchin Gururangan, Swabha Swayamdipta, Omer Levy, Roy Schwartz, Samuel R. Bowman, and Noah A. Smith. 2018. Annotation artifacts in natural language inference data. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers)*, pages 107–112.

Simeng Han, Hailey Schoelkopf, Yilun Zhao, Zhenting Qi, Martin Riddell, Wenfei Zhou, James Coady, David Peng, Yujie Qiao, Luke Benson, Lucy Sun, Alexander Wardle-Solano, Hannah Szabó, Ekaterina Zubova, Matthew Burtell, Jonathan Fan, Yixin Liu, Brian Wong, Malcolm Sailor, and 16 others. 2024. FOLIO: Natural language reasoning with first-order logic. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 22017–22031.

Wenyue Hua, Tyler Wong, Fei Sun, Liangming Pan, Adam Jardine, and William Yang Wang. 2025. InductionBench: LLMs fail in the simplest complexity class. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 26526–26546.

Zhengbao Jiang, Jun Araki, Haibo Ding, and Graham Neubig. 2021. How can we know when language models know? On the calibration of language models for question answering. *Transactions of the Association for Computational Linguistics*, 9:962–977.

Julie Kallini, Isabel Papadimitriou, Richard Futrell, Kyle Mahowald, and Christopher Potts. 2024. Mission: Impossible language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 14691–14714.

Najoung Kim and Tal Linzen. 2020. COGS: A compositional generalization challenge based on semantic interpretation. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 9087–9105.

Polina Kirichenko, Mark Ibrahim, Kamalika Chaudhuri, and Samuel J. Bell. 2025. AbstentionBench: Reasoning LLMs fail on unanswerable questions. In *Advances in Neural Information Processing Systems*, volume 38. Curran Associates, Inc. Datasets and Benchmarks Track.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. 2023. Efficient memory management for large language model serving with PagedAttention. In *Proceedings of the 29th Symposium on Operating Systems Principles*, SOSP '23, pages 611–626. Association for Computing Machinery.

Brenden Lake and Marco Baroni. 2018. Generalization without systematicity: On the compositional skills of sequence-to-sequence recurrent networks. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 2873–2882. PMLR.

Bingzhi Li, Lucia Donatelli, Alexander Koller, Tal Linzen, Yuekun Yao, and Najoung Kim. 2023. SLOG: A structural generalization benchmark for semantic parsing. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 3213–3232.

Alisa Liu, Zhaofeng Wu, Julian Michael, Alane Suhr, Peter West, Alexander Koller, Swabha Swayamdipta, Noah A. Smith, and Yejin Choi. 2023. We're afraid language models aren't modeling ambiguity. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 790–807.

Malik Marmonier, Rachel Bawden, and Benoît Sagot. 2025. Explicit learning and the LLM in machine translation. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 31372–31422.

Tom M. Mitchell. 1982. Generalization as search. *Artificial Intelligence*, 18(2):203–226.

Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, Jake Vanderplas, Alexandre Passos, David Cournapeau, Matthieu Brucher, Matthieu Perrot, and Édouard Duchesnay. 2011. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12(85):2825–2830.

Qwen Team. 2026. Qwen3.5: Towards native multimodal agents. Qwen blog.

Laura Ruis, Jacob Andreas, Marco Baroni, Diane Bouchacourt, and Brenden M. Lake. 2020. A benchmark for systematic generalization in grounded language understanding. In *Advances in Neural Information Processing Systems*, volume 33, pages 19861–19872. Curran Associates, Inc.

Gözde Gül Şahin, Yova Kementchedjhieva, Phillip Rust, and Iryna Gurevych. 2020. PuzzLing machines: A challenge on learning from small data. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 1241–1254.

Eduardo Sánchez, Belen Alastruey, Christophe Ropers, Arina Turkatenko, Pontus Stenetorp, Mikel Artetxe, and Marta R. Costa-jussà. 2025. Linguini: A benchmark for language-agnostic linguistic reasoning. In *Advances in Neural Information Processing Systems*, volume 38. Curran Associates, Inc. Datasets and Benchmarks Track.

Garrett Tanzer, Mirac Suzgun, Eline Visser, Dan Jurafsky, and Luke Melas-Kyriazi. 2024. A benchmark for learning to translate a new language from one grammar book. In *International Conference on Learning Representations*, volume 2024, pages 18955–18985.

Josef Valvoda, Naomi Saphra, Jonathan Rawski, Adina Williams, and Ryan Cotterell. 2022. Benchmarking compositionality with formal languages. In *Proceedings of the 29th International Conference on Computational Linguistics*, pages 6007–6018.

Frank Wildenburg, Michael Hanna, and Sandro Pezzelle. 2024. Do pre-trained language models detect and understand semantic underspecification? Ask the DUST! In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 9598–9613.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, and 3 others. 2020. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 38–45. Association for Computational Linguistics.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, and 41 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, Kai Dang, and 23 others. 2024. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*.

Chen Zhang, Xiao Liu, Jiuheng Lin, and Yansong Feng. 2024. Teaching large language models an unseen language on the fly. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 8783–8800.

Zihao Zhao, Eric Wallace, Shi Feng, Dan Klein, and Sameer Singh. 2021. Calibrate before use: Improving few-shot performance of language models. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings*

of Machine Learning Research, pages 12697–12706. PMLR.

A Formal Semantics and Certificates

Proof of evidence-relative necessity. Choose $a \neq b$ in $A_t(q, E)$. By definition, there are $h_a, h_b \in \mathcal{V}_e(E)$ such that $f_t(h_a, q) = a$ and $f_t(h_b, q) = b$. The learner receives the same declared class, evidence, and query whether the hidden true language is h_a or h_b, yet a single payload cannot be correct in both worlds. Therefore no learner with only those inputs can guarantee a correct payload for every compatible true language. □

Exact decision algorithm. The oracle enumerates all 256 assignments to the ordered lexical–grammar bit vector, retains the 128 assignments satisfying the public Boolean program, filters those candidates by the three observed dictionary facts, and executes the query under each of the 16 survivors. It returns `ANSWER` only when the resulting canonical payload set is a singleton. Otherwise it returns `ABSTAIN` and stores two surviving hypothesis IDs with distinct payloads. Hashes bind the canonical program, evidence, query, declared class, survivor set, answer-support partition, and complete certificate. Appendix K and Figure 5 run that algorithm end to end on the frozen pair of Figure 1, so every elimination and both readouts can be repeated by hand from the prompt alone.

Independent reconstruction. The clean-room auditor uses only the Python standard library and imports no SILICA package. It reparses the Boolean DSL, enumerates all programs and observations, reconstructs the 16 survivors and support partition, and checks the stored certificates by item ID. It additionally rebuilds the private template registry and route schedule, so agreement is not merely a second call to the generator's oracle.

B Four Real Complementary Query Pairs

Table 4 reports one immutable same-state pair from each mechanism family. Within each row, the hypothesis declaration and projected observations are identical across the two queries, so Query A and Query B share exactly the same 16 survivors. The structured query, response task, and task-conditioned response schema change together to target the complementary coordinate.

For the parity pair visualized in Figure 1, the two exact response objects are

```
{"decision":"ANSWER","answer":"fox"}
{"decision":"ABSTAIN","answer":null}.
```

Any prose, Markdown fence, additional key, wrong payload type, or non-JSON value is invalid. For the underdetermined row, the hidden sampled target happens to be subject-initial, but that field is not an answer: the other eight compatible languages are verb-initial. This distinction is why target accuracy is not the benchmark objective.

B.1 Complete renderer messages for Figure 1

Figure 1 uses a readable, faithful excerpt. The files below are generated directly from the frozen renderer. Machine-exact JSON arrays are checked in beside these losslessly wrapped views. To reconstruct each exact message string, concatenate the content lines between its `BEGIN`/`END` markers and remove only the display line feeds; the wrapper also records a content SHA-256. Both rows belong to `hard-v2-state-b1e9ee8eb2baed19aee4`.

Complete ANSWER input. Item `silica-d8de6e0dbb2c8bd57d7c8bd9` has prompt SHA-256 `7d29fc3adf69506064c959c3996a661d2d881e1f67b83abee63e3f77682a61cb`.

```
LOSSLESS DISPLAY: concatenate content lines between
↪  BEGIN/END; remove only LF.
The BEGIN/END wrapper lines are metadata and are not part of
↪  message content.
BEGIN MESSAGE 0 role=system content_sha256=b10f321447f2fbe3
↪  b973a8fc079908a2595ea5aefd23028bded201395d9a6e27
You are solving the SILICA-Hard posterior-matched
↪  paired-query identifiability reasoning
 benchmark. The supplied declaration defines an exact finite
 ↪  hypothesis class: enumerate
 all Boolean feature assignments, retain only assignments
 ↪  accepted by every declared Boo
lean-program constraint, and then retain only assignments
↪  consistent with every observed
 form/meaning pair. Evaluate the query under every surviving
 ↪  assignment. Return ANSWER o
nly if all survivors produce one identical canonical answer;
↪  otherwise return ABSTAIN. R
eason silently. Emit exactly one JSON object satisfying
↪  canonical_response_schema, with
no markdown, rationale, confidence, or additional keys.
END MESSAGE 0
BEGIN MESSAGE 1 role=user content_sha256=9136ef53746dacd521
↪  2d3d3db6b8f8850ce946b70a014f4a4c69e284ac8909ee
{"adapter_protocol_hash":"eb211b7350e62a6eadae8f3f5ce73d7e1
↪  536cc10c9984e342763989394f84c
5f","adapter_task":"hard_posterior_matched","adapter_versio
↪  n":"silica-hard-pair-aware-ad
apter-v2","canonical_response_schema":{"oneOf":[{"additiona
↪  lProperties":false,"propertie
s":{"answer":{"enum":["fox","owl","dog","bear"],"type":"str
↪  ing"},"decision":{"enum":["AN
SWER"],"type":"string"}},"required":["decision","answer"],"
↪  type":"object"},{"additionalP
roperties":false,"properties":{"answer":{"type":"null"},"de
↪  cision":{"enum":["ABSTAIN"],"
type":"string"}},"required":["decision","answer"],"type":"o
↪  bject"}],"type":"object"},"de
cision_rule":{"ABSTAIN":"at least two observation-compatible
↪  hypotheses have different c
anonical query answers","ANSWER":"every
↪  observation-compatible hypothesis has the same c
anonical query answer"},"hypothesis_declaration":{"base_cla
↪  ss_size":256,"boolean_dsl_sem
antics":{"canonicalization":{"arities":{"and":"at least
↪  2","eq":2,"implies":2,"ite":3,"n
```

Table 4: Real SILICA examples, joined by item ID to evaluator-only gold. Counts are exact support among the same 16 survivors. Witness IDs are included only here for explanation and never enter the model prompt.

Family	Shared model-visible evidence	Query with unanimous support	Complementary query with disagreement
Equality chain	`nipu`→`dog`; `rilu`→`red`; `mabo`→`see`	order family → `ANSWER(subject_initial)`, 16/16	meaning of `hepu` → `ABSTAIN`; fox 8/16 vs. owl 8/16; witnesses h008/h009
Majority guard	`rase`→`dog`; `kuhe`→`see`; `toze`→`red`	order family → `ANSWER(subject_initial)`, 16/16	meaning of `puso` → `ABSTAIN`; fox 8/16 vs. owl 8/16; witnesses h014/h015
Parity guard	`pudo`→`red`; `levu`→`see`; `reze`→`dog`	meaning of `helu` → `ANSWER(fox)`, 16/16	order family → `ABSTAIN`; subject-initial 8/16 vs. verb-initial 8/16; witnesses h002/h018
Selector multiplexer	`devi`→`dog`; `babe`→`see`; `naga`→`red`	meaning of `mivu` → `ANSWER(fox)`, 16/16	order family → `ABSTAIN`; subject-initial 8/16 vs. verb-initial 8/16; witnesses h004/h020


```
ot":1,"or":"at least 2","xor":"at least
↪  2"},"commutative_argument_order":"lexicographic
canonical JSON ordering for
↪  and/or/xor/eq","constraint_order":"lexicographic
↪  canonical J
SON ordering","object_keys":"lexicographic canonical JSON
↪  ordering"},"domain":"Boolean v
alues false/true, encoded by SILICA feature bits
↪  0/1","operators":{"and":"true iff every
 arg is true","const":"the literal Boolean value","eq":"true
 ↪  iff its two args have the s
ame Boolean value","implies":"equivalent to (not first) or
↪  second","ite":"second arg if
first arg is true, otherwise third arg","not":"Boolean
↪  negation of arg","or":"true iff a
t least one arg is true","var":"the Boolean bit of the named
↪  feature","xor":"true iff an
 odd number of args are true"},"program_acceptance":"a
 ↪  hypothesis is admitted iff every
constraint evaluates to true"},"boolean_program":{"constrai
↪  nts":[{"args":[{"args":[{"arg
":{"args":[{"args":[{"name":"modifier_swap_01","op":"var"},
↪  {"name":"noun_swap_23","op":"
var"},{"name":"verb_swap_01","op":"var"}],"op":"xor"},{"arg
↪  s":[{"name":"modifier_swap_01
","op":"var"},{"name":"verb_swap_01","op":"var"}],"op":"eq"
↪  }],"op":"and"},"op":"not"},{"
args":[{"args":[{"name":"verb_swap_01","op":"var"},{"name":
↪  "noun_swap_23","op":"var"},{"
arg":{"name":"modifier_swap_01","op":"var"},"op":"not"}],"o
↪  p":"ite"},{"name":"order_fami
ly","op":"var"}],"op":"eq"}],"op":"implies"},{"args":[{"arg
↪  s":[{"args":[{"name":"modifie
r_swap_01","op":"var"},{"name":"noun_swap_23","op":"var"},{
↪  "name":"verb_swap_01","op":"v
ar"}],"op":"xor"},{"args":[{"name":"modifier_swap_01","op":
↪  "var"},{"name":"verb_swap_01"
,"op":"var"}],"op":"eq"}],"op":"and"},{"args":[{"args":[{"n
↪  ame":"noun_swap_23","op":"var
"},{"name":"verb_swap_01","op":"var"},{"name":"modifier_swa
↪  p_01","op":"var"}],"op":"ite"
},{"name":"noun_swap_01","op":"var"}],"op":"eq"}],"op":"imp
↪  lies"}],"op":"and"}],"dsl_ver
sion":"silica-boolean-constraint-program-v1","variables":["
↪  noun_swap_01","noun_swap_23",
"verb_swap_01","modifier_swap_01","order_family","order_var
↪  iant","alignment","agreement"
]},"class_size":128,"constant_markers":{"agreement_plural":
↪  "poso","agreement_singular":"
sena","case_slot_a":"hopo","case_slot_b":"tabu","past_suffi
↪  x":"vagi","plural_suffix":"pe
pu","preverbal_negation":"dare"},"constant_rules":["modifie
↪  rs precede nouns","plural and
 case are suffixes","past precedes agreement on the
 ↪  verb"],"exact_enumeration":{"allowli
st_required":false,"filter":"retain assignments satisfying
↪  every Boolean-program constra
int","universe":"all 2^8 assignments in
↪  feature_variables_lsb_to_msb order"},"feature_va
riables_lsb_to_msb":[{"kind":"lexical","name":"noun_swap_01
↪  ","values":["identity","swapp
ed"]},{"kind":"lexical","name":"noun_swap_23","values":["id
↪  entity","swapped"]},{"kind":"
lexical","name":"verb_swap_01","values":["identity","swappe
↪  d"]},{"kind":"lexical","name"
:"modifier_swap_01","values":["identity","swapped"]},{"kind
↪  ":"grammar","name":"order_fam
ily","values":["subject_initial","verb_initial"]},{"kind":"
↪  grammar","name":"order_varian
t","values":["variant_a","variant_b"]},{"kind":"grammar","n
↪  ame":"alignment","values":["n
ominative_accusative","ergative_absolutive"]},{"kind":"gram
↪  mar","name":"agreement","valu
es":["zero","agent_number"]}],"fixed_lexicon":[{"category":
↪  "verb","form":"petu","meaning
":"chase"},{"category":"verb","form":"mizu","meaning":"slee
↪  p","valency":"intransitive"},
{"category":"modifier","form":"zabu","meaning":"green"},{"c
↪  ategory":"modifier","form":"n
upo","meaning":"small"}],"grammar_axes":[{"name":"order_fam
↪  ily","values":["subject_initi
al","verb_initial"]},{"name":"order_variant","values":["var
↪  iant_a","variant_b"]},{"name"
:"alignment","values":["nominative_accusative","ergative_ab
↪  solutive"]},{"name":"agreemen
t","values":["zero","agent_number"]}],"grammar_semantics":{
↪  "agreement_mapping":{"agent_n
umber":{"plural":"agreement_plural","singular":"agreement_s
↪  ingular"},"zero":"no_agreemen
t_suffix"},"alignment_mapping":{"ergative_absolutive":{"int
↪  ransitive_subject_S":"case_sl
ot_b","transitive_agent_A":"case_slot_a","transitive_patien
↪  t_O":"case_slot_b"},"nominati
ve_accusative":{"intransitive_subject_S":"case_slot_a","tra
↪  nsitive_agent_A":"case_slot_a
","transitive_patient_O":"case_slot_b"}},"intransitive_orde
↪  r":{"subject_initial":"SV","v
erb_initial":"VS"},"order_mapping":[{"order_family":"subjec
↪  t_initial","order_variant":"v
ariant_a","word_order":"SVO"},{"order_family":"subject_init
↪  ial","order_variant":"variant
_b","word_order":"SOV"},{"order_family":"verb_initial","ord
↪  er_variant":"variant_a","word
_order":"VSO"},{"order_family":"verb_initial","order_varian
↪  t":"variant_b","word_order":"
VOS"}]},"lexical_axes":[{"category":"noun","constraint":"ei
↪  ther_bijection","forms":["hel
u","vuga"],"name":"noun_pair_01","possible_meanings":["fox"
↪  ,"owl"]},{"category":"noun","
constraint":"either_bijection","forms":["kuri","reze"],"nam
↪  e":"noun_pair_23","possible_m
eanings":["dog","bear"]},{"category":"verb","constraint":"e
↪  ither_bijection","forms":["le
vu","bati"],"name":"verb_pair_01","possible_meanings":["see
↪  ","help"]},{"category":"modif
ier","constraint":"either_bijection","forms":["pudo","gisu"
↪  ],"name":"modifier_pair_01","
possible_meanings":["red","blue"]}],"schema_family":"silica
↪  -hard-posterior-matched-v2","
type":"closed_world_posterior_matched_boolean_program_subse
↪  t"},"observations":[{"categor
y":"modifier","channel":"dictionary","form":"pudo","semanti
↪  c":"red"},{"category":"verb",
"channel":"dictionary","form":"levu","semantic":"see"},{"ca
↪  tegory":"noun","channel":"dic
tionary","form":"reze","semantic":"dog"}],"prompt_version":
↪  "silica-hard-posterior-matche
d-json-v2","query":{"category":"noun","form":"helu"},"respo
↪  nse_schema_version":"silica-a
nswer-json-schema-v2","response_task":"lexicon"}
END MESSAGE 1
```


Exact ANSWER gold object.


```
{
  "answer": "fox",
  "decision": "ANSWER"
}
```

Complete ABSTAIN input. Item `silica-4df031b78b218b09cff975e2` has prompt SHA-256 `5a1cb07dc66456f83b275de957a04386 26ec024da9e5c14d74209ca94b2ce414`.

```
LOSSLESS DISPLAY: concatenate content lines between
↪ BEGIN/END; remove only LF.
The BEGIN/END wrapper lines are metadata and are not part of
↪ message content.
BEGIN MESSAGE 0 role=system content_sha256=b10f321447f2fbe3
↪ b973a8fc079908a2595ea5aefd23028bded201395d9a6e27
You are solving the SILICA-Hard posterior-matched
↪ paired-query identifiability reasoning
 benchmark. The supplied declaration defines an exact finite
 ↪ hypothesis class: enumerate
 all Boolean feature assignments, retain only assignments
 ↪ accepted by every declared Boo
lean-program constraint, and then retain only assignments
↪ consistent with every observed
 form/meaning pair. Evaluate the query under every surviving
 ↪ assignment. Return ANSWER o
nly if all survivors produce one identical canonical answer;
↪ otherwise return ABSTAIN. R
eason silently. Emit exactly one JSON object satisfying
↪ canonical_response_schema, with
no markdown, rationale, confidence, or additional keys.
END MESSAGE 0
BEGIN MESSAGE 1 role=user content_sha256=3b456bde71620707fd
↪ e7be24f4db44f7e9be460f504c279dc1383a3c8f43cd69
{"adapter_protocol_hash":"eb211b7350e62a6eadae8f3f5ce73d7e1
↪ 536cc10c9984e342763989394f84c
5f","adapter_task":"hard_posterior_matched","adapter_versio
↪ n":"silica-hard-pair-aware-ad
apter-v2","canonical_response_schema":{"oneOf":[{"additiona
↪ lProperties":false,"propertie
s":{"answer":{"enum":["subject_initial","verb_initial"],"ty
↪ pe":"string"},"decision":{"en
um":["ANSWER"],"type":"string"}},"required":["decision","an
↪ swer"],"type":"object"},{"add
itionalProperties":false,"properties":{"answer":{"type":"nu
↪ ll"},"decision":{"enum":["ABS
TAIN"],"type":"string"}},"required":["decision","answer"],"
↪ type":"object"}],"type":"obje
ct"},"decision_rule":{"ABSTAIN":"at least two
↪ observation-compatible hypotheses have dif
ferent canonical query answers","ANSWER":"every
↪ observation-compatible hypothesis has th
e same canonical query answer"},"hypothesis_declaration":{"
↪ base_class_size":256,"boolean
_dsl_semantics":{"canonicalization":{"arities":{"and":"at
↪ least 2","eq":2,"implies":2,"i
te":3,"not":1,"or":"at least 2","xor":"at least
↪ 2"},"commutative_argument_order":"lexico
graphic canonical JSON ordering for
↪ and/or/xor/eq","constraint_order":"lexicographic can
onical JSON ordering","object_keys":"lexicographic canonical
↪ JSON ordering"},"domain":"B
oolean values false/true, encoded by SILICA feature bits
↪ 0/1","operators":{"and":"true i
ff every arg is true","const":"the literal Boolean
↪ value","eq":"true iff its two args ha
ve the same Boolean value","implies":"equivalent to (not
↪ first) or second","ite":"second
 arg if first arg is true, otherwise third
 ↪ arg","not":"Boolean negation of arg","or":"tr
ue iff at least one arg is true","var":"the Boolean bit of
↪ the named feature","xor":"tru
e iff an odd number of args are
↪ true"},"program_acceptance":"a hypothesis is admitted if
f every constraint evaluates to
↪ true"},"boolean_program":{"constraints":[{"args":[{"args
":[{"arg":{"args":[{"args":[{"name":"modifier_swap_01","op"
↪ :"var"},{"name":"noun_swap_23
","op":"var"},{"name":"verb_swap_01","op":"var"}],"op":"xor
↪ "},{"args":[{"name":"modifier
_swap_01","op":"var"},{"name":"verb_swap_01","op":"var"}],"
↪ op":"eq"}],"op":"and"},"op":"
not"},{"args":[{"args":[{"name":"verb_swap_01","op":"var"},
↪ {"name":"noun_swap_23","op":"
var"},{"arg":{"name":"modifier_swap_01","op":"var"},"op":"n
↪ ot"}],"op":"ite"},{"name":"or
der_family","op":"var"}],"op":"eq"}],"op":"implies"},{"args
↪ ":[{"args":[{"args":[{"name":
"modifier_swap_01","op":"var"},{"name":"noun_swap_23","op":
↪ "var"},{"name":"verb_swap_01"
,"op":"var"}],"op":"xor"},{"args":[{"name":"modifier_swap_0
↪ 1","op":"var"},{"name":"verb_
swap_01","op":"var"}],"op":"eq"}],"op":"and"},{"args":[{"ar
↪ gs":[{"name":"noun_swap_23","
op":"var"},{"name":"verb_swap_01","op":"var"},{"name":"modi
↪ fier_swap_01","op":"var"}],"o
p":"ite"},{"name":"noun_swap_01","op":"var"}],"op":"eq"}],"
↪ op":"implies"}],"op":"and"}],
"dsl_version":"silica-boolean-constraint-program-v1","varia
↪ bles":["noun_swap_01","noun_s
wap_23","verb_swap_01","modifier_swap_01","order_family","o
↪ rder_variant","alignment","ag
reement"]},"class_size":128,"constant_markers":{"agreement_
↪ plural":"poso","agreement_sin
gular":"sena","case_slot_a":"hopo","case_slot_b":"tabu","pa
↪ st_suffix":"vagi","plural_suf
fix":"pepu","preverbal_negation":"dare"},"constant_rules":[
↪ "modifiers precede nouns","pl
ural and case are suffixes","past precedes agreement on the
↪ verb"],"exact_enumeration":{
"allowlist_required":false,"filter":"retain assignments
↪ satisfying every Boolean-program
 constraint","universe":"all 2^8 assignments in
 ↪ feature_variables_lsb_to_msb order"},"fe
ature_variables_lsb_to_msb":[{"kind":"lexical","name":"noun
↪ _swap_01","values":["identity
","swapped"]},{"kind":"lexical","name":"noun_swap_23","valu
↪ es":["identity","swapped"]},{
"kind":"lexical","name":"verb_swap_01","values":["identity"
↪ ,"swapped"]},{"kind":"lexical
","name":"modifier_swap_01","values":["identity","swapped"]
↪ },{"kind":"grammar","name":"o
rder_family","values":["subject_initial","verb_initial"]},{
↪ "kind":"grammar","name":"orde
r_variant","values":["variant_a","variant_b"]},{"kind":"gra
↪ mmar","name":"alignment","val
ues":["nominative_accusative","ergative_absolutive"]},{"kin
↪ d":"grammar","name":"agreemen
t","values":["zero","agent_number"]}],"fixed_lexicon":[{"ca
↪ tegory":"verb","form":"petu",
"meaning":"chase"},{"category":"verb","form":"mizu","meanin
↪ g":"sleep","valency":"intrans
itive"},{"category":"modifier","form":"zabu","meaning":"gre
↪ en"},{"category":"modifier","
form":"nupo","meaning":"small"}],"grammar_axes":[{"name":"o
↪ rder_family","values":["subje
ct_initial","verb_initial"]},{"name":"order_variant","value
↪ s":["variant_a","variant_b"]}
,{"name":"alignment","values":["nominative_accusative","erg
↪ ative_absolutive"]},{"name":"
agreement","values":["zero","agent_number"]}],"grammar_sema
↪ ntics":{"agreement_mapping":{
"agent_number":{"plural":"agreement_plural","singular":"agr
↪ eement_singular"},"zero":"no_
agreement_suffix"},"alignment_mapping":{"ergative_absolutiv
↪ e":{"intransitive_subject_S":
"case_slot_b","transitive_agent_A":"case_slot_a","transitiv
↪ e_patient_O":"case_slot_b"},"
nominative_accusative":{"intransitive_subject_S":"case_slot
↪ _a","transitive_agent_A":"cas
e_slot_a","transitive_patient_O":"case_slot_b"}},"intransit
↪ ive_order":{"subject_initial"
:"SV","verb_initial":"VS"},"order_mapping":[{"order_family"
↪ :"subject_initial","order_var
iant":"variant_a","word_order":"SVO"},{"order_family":"subj
↪ ect_initial","order_variant":
"variant_b","word_order":"SOV"},{"order_family":"verb_initi
↪ al","order_variant":"variant_
a","word_order":"VSO"},{"order_family":"verb_initial","orde
↪ r_variant":"variant_b","word_
order":"VOS"}]},"lexical_axes":[{"category":"noun","constra
↪ int":"either_bijection","form
s":["helu","vuga"],"name":"noun_pair_01","possible_meanings
↪ ":["fox","owl"]},{"category":
"noun","constraint":"either_bijection","forms":["kuri","rez
↪ e"],"name":"noun_pair_23","po
ssible_meanings":["dog","bear"]},{"category":"verb","constr
↪ aint":"either_bijection","for
ms":["levu","bati"],"name":"verb_pair_01","possible_meaning
↪ s":["see","help"]},{"category
":"modifier","constraint":"either_bijection","forms":["pudo
↪ ","gisu"],"name":"modifier_pa
ir_01","possible_meanings":["red","blue"]}],"schema_family"
↪ :"silica-hard-posterior-match
ed-v2","type":"closed_world_posterior_matched_boolean_progr
↪ am_subset"},"observations":[{
"category":"modifier","channel":"dictionary","form":"pudo",
↪ "semantic":"red"},{"category"
:"verb","channel":"dictionary","form":"levu","semantic":"se
↪ e"},{"category":"noun","chann
el":"dictionary","form":"reze","semantic":"dog"}],"prompt_v
↪ ersion":"silica-hard-posterio
r-matched-json-v2","query":{"feature":"order_family"},"resp
↪ onse_schema_version":"silica-
answer-json-schema-v2","response_task":"grammar_feature"}
END MESSAGE 1
```

Table 5: The renderer enforces a strict public/private boundary.

Model-visible	Evaluator-only
Boolean DSL semantics and program; feature values and realization rules; three dictionary facts; query; decision rule; exact response schema	Family, route, template and pair metadata; observation IDs; semantic and structural hashes; hidden role orientation; target language and target answer; gold decision and payload; survivors, supports, witnesses, and certificates

Exact ABSTAIN gold object.

```
{
  "answer": null,
  "decision": "ABSTAIN"
}
```

The ANSWER prompt's task, structured query, and schema request a noun meaning; the ABSTAIN prompt's corresponding fields request a grammar feature. Their hypothesis declaration and projected observations are identical. Neither prompt contains survivor counts, support partitions, witnesses, or gold.

B.2 Field boundary

Public files contain routing fields needed to assemble complete cohorts. The prompt renderer explicitly projects them away; the evaluator joins private gold only after the public cohort and its hash are frozen.

C Guard Families and Semantic Packing

Let $g(X)$ be a guard over the three observed bits, let Q and N be the two query-facing coordinates, and let $p(X)$ and $n(X)$ be their payload expressions. Table 6 gives the exact placeholder skeletons before variable permutation and canonicalization. All four encode the same switch—g constrains Q, while $\neg g$ constrains N—through different Boolean AST structures.

Candidate enumeration produces 914 parity, 1,112 majority, 268 equality, and 350 selector programs. Their union contains 2,411 globally unique paired behaviors. Filtering against the fixed 12-template support registry at length-16 ternary paired-signature distance at least four positions leaves 854, 1,021, 229, and 340 candidates, respectively. A standard-library deterministic search checks all 24 family orders under two fixed conflict-degree scores. The best complete balanced cycle contains 57 templates per family; the release selects 48.

The paired signature records the outcome of both query roles in each of the eight observed-bit states as `ABSTAIN`, `ANSWER:0`, or `ANSWER:1`. Evaluation–evaluation and evaluation–support minimum distance is four under both this signature and the derived full-class truth table. All 192 evaluation template semantics are unique.

C.1 Routes and complete units

For each template, route j selects sorted member $j \bmod |\text{stratum}|$ from each of four strata: active/inactive guard crossed with payload 0/1. A route contains four states and both query roles, forming one eight-row paired group. Across eight routes, every template covers all eight observed-bit states; each stratum contributes exactly eight selections, and members receive their floor-or-ceiling share. The common model cohort contains one route per template. Only the full cohort contains all eight routes per template.

D Construction and Shortcut Audits

The learned probes remove identifiers, hashes, routes, and observation surface forms while retaining the public query and Boolean program. Template folds are grouped eight ways and family folds four ways; each of the four predeclared probes is exactly at the 0.500 acceptance gate. These audits exclude the tested shortcut families, not every possible heuristic.

E Metrics, Uncertainty, and Training Signals

Every report includes exact numerators and denominators for strict joint accuracy, balanced strict joint accuracy, decision accuracy, balanced decision accuracy, ANSWER and ABSTAIN recall, exact payload recall, answer coverage, format validity, false certainty, false abstention, and request errors. Breakdowns retain mechanism family, public query axis, and route.

At the four-row level, the evaluator requires the complete oriented decision pattern and, separately, both answerable payloads. At the paired level, it requires both orientations, all eight strict responses, and all four same-state query-complement edges. Unoriented complement and factorial consistency are structural diagnostics only: a globally inverted predictor can satisfy them.

Intervals use 10,000 percentile replicates with seed 20260803. Each replicate resamples the 48 semantic templates within each of the four mechanism families and moves every associated route,




Figure 3: **Rows are nested views, not independent examples.** Panel A reports the exact evaluation hierarchy; inference resamples 192 semantic templates within four 48-template mechanism families. Panel B shows exact nuisance balance and shortcut gates. Panel C reports the sealed packing at the selected $d = 4$: the search found 57 templates per family, released 48, and retained nine of measured headroom. The length-16 ternary signatures differ in at least four positions. These are properties of one fixed finite registry, not a population estimate or an unreported search frontier.

Table 6: Four structural encodings of the guarded-switch principle.

Family	Canonical constraint skeleton	Characteristic root
Parity guard	$(g \Rightarrow Q = p) \wedge (\neg g \Rightarrow N = n)$	implication
Majority guard	$(\neg g \vee Q = p) \wedge (g \vee N = n)$	disjunction
Equality chain	$[(g \wedge Q) = (g \wedge p)] \wedge [(\neg g \wedge N) = (\neg g \wedge n)]$	equality
Selector multiplexer	$\mathrm{ITE}(g, Q = p, N = n)$	if–then–else

Table 7: Frozen release checks, all over the complete 12,288-row artifact.

Check	Exact result
In-generator label/payload oracle	12,288/12,288
Independent clean-room oracle	12,288/12,288
Declared class size 128	12,288/12,288
Posterior size 16	12,288/12,288
Same-state opposite-action pairs	6,144/6,144
Unique rendered prompt hashes	12,288/12,288
Reverse-order ID join	identical
Query-masked raw-state control	6,144/12,288
Word, held-out-template	6,144/12,288
Character, held-out-template	6,144/12,288
Word, held-out-family	6,144/12,288
Character, held-out-family	6,144/12,288

state, and query together. The intervals therefore describe sensitivity over this finite registry; they are neither independent-row confidence intervals nor hypothesis tests.

Reference levels for the two derived diagnostics. The decision signal $\mathrm{AR} - \mathrm{FCR}$ and conditional payload accuracy $\mathrm{CPA} = \mathrm{EAR}/\mathrm{AR}$ are reported because AR, UR and EAR each mix a model's chosen answer coverage with its actual competence. Consider a predictor that emits `ANSWER` with probability α independently of the row. It attains $\mathrm{AR} = \mathrm{FCR} = \alpha$, hence decision signal 0 and, on format-valid rows, $\mathrm{BDA} = 1/2$ for every α; its $\mathrm{UR} = 1 - \alpha$ and $\mathrm{EAR} = \alpha/2$ nevertheless sweep the entire range as α varies, and its BJA sweeps $[.25, .50]$. Reporting UR, EAR or BJA alone therefore cannot distinguish a competent model from a differently tuned constant. The CPA reference of exactly $1/2$ is a property of the construction rather than an asymptotic argument: in all 3,072 four-cell units the two answerable rows carry different canonical payloads, verified directly against the sealed gold records.

Sealed model ledger. Model numbers in the main text are not transcribed. A collector reverifies each archive (zero-error completion status, UUID agreement, dataset release identity, cohort identity, per-file SHA-256 against the completion record, evaluator report hash, bootstrap replicate count and seed, declared row count, mechanism-family strata, and runtime node) and emits one canonical ledger carrying its own payload digest. The panel table and panel figure are both generated from that ledger, and the figure script recomputes the digest and refuses to draw on mismatch. Any archive that is

partial, nonzero-error, or hash-inconsistent is rejected rather than downweighted.

RL-ready, not an RL result. The official scorer yields deterministic row rewards for schema validity, decision correctness, and exact joint correctness, plus sparse all-four and all-eight group rewards. These components can support supervised learning, rejection sampling, or reinforcement learning without a judge model. Private support partitions and witnesses can additionally supervise a future certificate-producing agent. The current direct response contract requests only decision and payload, and this paper reports no policy optimization, training curve, agent trajectory, or transfer claim.

F Direct-Model and Provenance Protocol

The frozen common panel evaluates Qwen2.5-Instruct at 0.5B, 1.5B, 3B, 7B, 14B, and 32B parameters, Phi-3.5-mini-instruct, and SmolLM2-1.7B-Instruct on the same 1,536 rows. Qwen2.5-14B additionally runs on all 12,288 rows; Qwen2.5-32B is the stronger common-cohort sentinel; and Qwen2.5-1.5B receives one ID-joined cross-hardware replicate. Revisions are immutable 40-character repository commits. An additional reasoning model may be reported only under a separately frozen, complete, provenance-valid condition; exploratory or partial output is never merged with the panel.

Each condition in the frozen original local panel uses one CUDA GPU, bfloat16, batch size two, greedy decoding, temperature and seed zero, at most 384 new tokens, left padding, the tokenizer chat template, and local files only. Tensor-parallel extensions are separate frozen conditions. Output must terminate with EOS. The parser preserves generated special-token IDs and rejects any special token inside the content span, a missing EOS, cap termination, prose, repair, or additional JSON keys.

Each local archive binds the dataset and public cohort, post-selection gold audit, prompt and schema, model and tokenizer revisions, a safetensors-only load plan, every weight/config/tokenizer file hash and size, effective generation configuration, source commit and executed source hashes, isolated runtime, hardware, token IDs, request hashes, and a canonical run UUID. Weight index paths must be normalized relative POSIX safetensors paths contained in the sealed manifest. Snapshot files remain descriptor-sealed through loading and are revalidated before output is appended. Any model, source, cache, or configuration drift aborts rather than silently defining a new condition.

Trace-permitted extension conditions. The trace-permitted conditions of Section 6 are served by vLLM 0.18.1 (Kwon et al., 2023) through the tokenizer chat template; thinking is toggled by the template's `enable_thinking` switch, the `deepseek_r1` reasoning parser separates the trace from the final content, and only the final content is parsed and scored. Within each matched pair the checkpoint files, revision, prompt messages, sampling settings, 16,384-token budget, seed and engine version are identical. The Qwen3-1.7B and Qwen3-235B pairs differ only in the thinking switch and the reasoning parser; both 235B servers load the same GPTQ checkpoint with the same Marlin GPTQ kernel, as their engine logs record. The Qwen3.5-2B decoding pair differs only in temperature and top-k. The two arms of each pair ran from different revisions of our evaluation harness; the changes concern how a response without final content is recorded (as an incorrect row rather than a request error) and how a run is admitted to its frozen configuration, not the request sent to the model. The Qwen3.5-0.8B and Qwen3.5-2B trace-on arms each lose one row to an adapter error in our harness, so the evaluator does not finalize them; we report only their termination rates and their strict format validity, computed with the evaluator's parser with the lost row counted as invalid.

Phi-3.5 with a multi-token stop contract. Under the local panel's single-EOS contract every Phi-3.5-mini response carries its end-of-turn token inside the scored span (1,536/1,536), so the sealed condition has no valid rows. A replacement condition keeps the checkpoint, revision, cohort, prompt, response schema and scoring, and serves the model through vLLM, which stops on the checkpoint's declared end-of-turn tokens; decoding is greedy with a 16,384-token budget. It reached 314 of the 1,536 rows within its time limit. All 126 responses that stop do so on the end-of-turn token, so the original artifact cannot recur, but only 49 of the 314 rows are strictly format-valid: 188 rows repeat one line until the token cap, and 77 of the 126 stopped rows break the output contract (35 surround the JSON object with prose, 13 wrap it in a code fence, and 29 are bare objects the strict parser rejects). A complete run could therefore not exceed

$(49 + 1{,}222)/1{,}536 < .83$, below the .95 gate, and the condition remains unevaluable.

Hosted inference is a separate stratum. Provider routing is pinned, fallbacks are disabled, the credential-free canonical request body is hashed, and request failures remain scored errors. A hosted result can enter a table only as a complete 1,536-row archive; quota-limited canaries do not receive a paper score.

G Reproducibility and Data Statement

Release. The code (generator, validators, clean-room oracle, prompt-only solver, shortcut audits and evaluator) is released under the Apache-2.0 license at a public code repository (link to follow). The dataset, with every model response analyzed in this paper, is released under CC BY 4.0 at a public Hugging Face dataset (link to follow); the model responses remain subject to the license of the model that produced them. The released files are byte-identical to the evaluated artifact. A few identifiers inside them predate the final name and are kept so that every hash below and every released response still matches: the version field reads `0.2.0-rc1`, grouping identifiers carry the prefix `hard-v2-`, and the model-facing system message and adapter string name the benchmark "SILICA-Hard".

Identities. The released artifact has the following SHA-256 identities.

Dataset aggregate	`d956532e42ecc666835f92071d779c7a d646b707b859794ffd91175d8d954b57`
Strict release	`f49ab76b635425db3ce60d69e3c2f13a 204f98a3f1e278778f7008570955c669`
Root manifest	`22032191c922fbbc424bfce0a7fe3dd9 96d040764dbc472c0e7432b5b4b58a15`
Public manifest	`01f0ae747baff9e04c6ef648bf461848 aded6636921f8d49a5b291db864d1c02`
Construction	`5f927888e9a0e7c58e0cd87e843cf69f 24249df53eb34b92a68ce72f3c1ce8c7`
Joined semantics	`f4f9e625dded0c0ee712012f14cd7ea3 ad4f896ec991c2389139412dc2d584dd`
Prompt equivalence	`cf36ed363351ffed8990c9f2ff14f095 5b6ad3eca08afbcdca6b7c42a62efb98`

The strict release identity binds the root and public manifests, all four public and four private shards, the complete file inventory, and `SHA256SUMS`; the prompt-equivalence identity binds the hash of every model-facing prompt under its semantic join. Same-seed regeneration is byte-identical. Every model run has its own run identifier, and no failed or restarted run is silently overwritten.

Data statement. All linguistic forms, programs, meanings, labels, supports, and witnesses are generated. The artifact contains no people, personal data, speaker labels, human annotations, or copyrighted corpus passages. Synthetic strings reduce direct textual contamination but not familiarity with logic-puzzle structure.

H Capability Map of Neighbouring Resources

I Decision Structure of the Registry

The structural unit is the published Boolean program, not the semantic template. Each of the 192 evaluation templates is instantiated as eight lexical–grammar routes, and every route publishes its own program, its own revealed feature triple, and its own pair of query-facing coordinates, so the registry holds **1,536 distinct programs** over the 12,288 rows, eight rows each. Our audit recovers each program's decision function *behaviourally*—by enumerating the declared universe and asking which query-facing coordinate is constant over the survivors—so the census does not depend on how a program happens to be spelled.

How many structurally different guards. The 1,536 programs realise **86 distinct three-bit decision functions** of the 256 possible: 32 occur in the majority-guard family, 31 in parity-guard, 24 in selector-multiplexer, and 14 in equality-chain. Those counts sum above 86 because the families are different encodings of one guarded-switch principle and do realise some of the same decision functions, which is the honest reading of the four-family design. No guard is unique to one program, and the most frequent covers 53 of 1,536 (3.5%), so memorising one guard transfers to almost nothing even before the held-out-template split.

What the decision actually costs. The two procedures differ by about three orders of magnitude, so the 2^8 framing should not be read as implying that the task is computationally deep. The *stated* enumerate-and-filter route costs 256 declared-universe assignments times the published program's operator count (median 22, range 6–40), a median of **5,632 operator evaluations** per row, before the sixteen survivor query evaluations. The *minimal sufficient* decision—which query-facing coordinate the evidence pins—is a Boolean function of the three revealed bits with minimal formula size **3 (median), at most 4** over the released DSL's own basis; 32 of the 1,536 programs need none at all. The gold decision is therefore at most four Boolean operations on three bits the prompt prints explicitly, which is why we read the silent




Figure 4: **A capability map, not a leaderboard.** Filled cells mark features explicitly stated as primary design features in the corresponding source; open cells mean only "not stated as a primary design feature," never inferiority or total absence. The columns cover in-context linguistic puzzles (Bean et al., 2024), ambiguity and underspecification (Liu et al., 2023; Wildenburg et al., 2024), explicit abstention (Kirichenko et al., 2025), and compositional semantic parsing (Kim and Linzen, 2020; Li et al., 2023). The source basis for every filled cell is released with the figure's source data.

panel's decision signal of $[-.010, +.017]$ as a failure to consult identifiability rather than an arithmetic shortfall.

Where the decision information lives. A compact rule that is available only *after* the program has been evaluated on the evidence is the task, not a leak. Two gradient-boosted probes (Friedman, 2001; Pedregosa et al., 2011) under the same grouped splits as the released controls make that checkable. A probe given the three revealed bits, the query role, the mechanism family, the response task and the declared class and posterior sizes—every evidence- and query-side feature except the guard value—scores balanced decision accuracy .500 under both the eight-fold held-out-template and the four-fold held-out-family split. The same probe additionally given the guard value scores 1.000 under both. The guard value is not a field of the input: obtaining it *is* evaluating the published program against the evidence, and a predictor that never performs that evaluation sits at chance whatever else it is given.

J Prompt Ablations on Two Panel Checkpoints

Four renderings of the same 1,536-row cohort were served from one Qwen2.5-14B endpoint and, separately, one Qwen2.5-32B endpoint, under greedy decoding at seed zero. `verbatim` is the released prompt; `scratchpad` keeps the user message byte-identical and replaces only the "reason silently" instruction with a `<think>` block and a 4,096-token budget, scored on the final JSON alone; `lean` keeps the system message and removes nine fields from the user message: the grammar realization block, the constant markers and rules, the fixed lexicon, the schema family, the adapter's protocol hash, task and version, and the response-schema version. This shortens the message by 25.3% on average while keeping the feature-value declaration, without which the task is undecidable; `compact_rule` keeps the user message byte-identical and replaces the enumerate-2^8 instruction with the guarded-switch route. Because it states structure the released prompt leaves to be inferred (though Section 3.3 publishes it), `compact_rule` is an upper bound on what relieving the stated procedure can buy, not a matched control.

Table 8: Prompt ablations on Qwen2.5-14B, 1,536 rows each. AR moves by a factor of 8.6 across arms while the decision signal never leaves $[-.007, +.004]$ and the all-eight endpoint stays at $0/192$.

Arm	Valid	AR	AR−FCR	CPA	BJA	Tok.
`verbatim`	.990	.466	+.004	.503	.382	18
`scratchpad`	.984	.730	−.007	.496	.307	697
`lean`	1.000	.203	−.005	.513	.448	18
`compact_rule`	.998	.085	+.003	.446	.477	13

These are exploratory and run outside the sealed evaluation stack, so `verbatim` is a validity check on the harness rather than a result: it reproduces the sealed panel row for each checkpoint to a maximum absolute difference of .023 (14B) and .0052 (32B) across strict format validity, AR, FCR, UR and BJA, which is also a transformers-to-vLLM replication of two panel conditions. `lean` is gated on decidability: the prompt-only solver still scores 12,288/12,288 on the reduced rendering, so the arm removes redundancy and not evidence.

The scratchpad arm is the informative one. Qwen2.5-14B writes a mean of 697 tokens of visible working per row, closes the block on 1,510/1,536 rows, and keeps .984 strict format validity, yet its decision signal is $-.007$ against $+.004$ for its verbatim twin on the same endpoint. What the trace buys is a higher answer rate, which *lowers* balanced strict joint accuracy from .382 to .307 by moving the policy toward the always-`ANSWER` constant. Together with the factor-isolation ladder this gives three points rather than one: a trace moves a reasoning-trained 235B, does not move a reasoning-trained 1.7B, and does not move a non-reasoning-trained 14B given a scratchpad and a budget.

Qwen2.5-32B, the panel's near-always-`ABSTAIN` checkpoint, gives the same picture from the low end of the answer-rate range. Across `verbatim`, `scratchpad`, `lean` and `compact_rule` its AR is .025, .845, .146 and .010, while its decision signal is $+.003$, $+.009$, $+.013$ and $+.001$ and the all-eight endpoint stays at $0/192$. Its scratchpad arm writes a mean of 832 tokens per row and closes the block on 1,502/1,536 rows, and again only raises AR, lowering balanced strict joint accuracy from .495 to .264.

K The Derivation, Step by Step

Figure 5 walks the complete derivation for the released parity item of Figure 1, in the order a solver must perform it. Panel 1 quotes the four fields of the single user message that carry the whole problem: the eight-bit feature inventory, the public Boolean program, the three dictionary facts, and the decision rule. Panel 2 performs the elimination: $2^8 = 256$ assignments, exactly half satisfying the program, then one halving per observed fact down to the 16-member version space. Panel 3 reads the two complementary queries off that shared set, including the guard evaluation that fixes one query-facing coordinate while leaving the other free, and a hand check of the two disagreeing witnesses as explicit bit vectors.

Every quantity in the figure is recomputed from the sealed artifact rather than transcribed, and the elimination counts are measured rather than assumed: each of the three facts halves the surviving set exactly. The construction guarantees this: every one of the eight observed-bit states leaves exactly 16 of the 128 declared languages, and the halving holds on all 12,288 rows. The figure also states the sufficiency result of Section 6: because every step shown is a field of that one message, a solver reading only the message reproduces all 12,288 rows exactly.

K.1 The exact instruction

The system message is identical for every scored row and states the procedure outright. It is reproduced here verbatim:

```
You are solving the SILICA-Hard
posterior-matched paired-query
identifiability reasoning
benchmark.  The supplied
declaration defines an exact
finite hypothesis class:
enumerate all Boolean feature
assignments, retain only
assignments accepted by every
declared Boolean-program
constraint, and then retain
only assignments consistent with
every observed form/meaning pair.
Evaluate the query under every
surviving assignment.  Return
ANSWER only if all survivors
produce one identical canonical
answer; otherwise return ABSTAIN.
Reason silently.  Emit exactly
one JSON object satisfying
canonical_response_schema,
with no markdown, rationale,
confidence, or additional keys.
```

The benchmark name inside this message is the one the evaluated models saw; like every other prompt byte, it is kept unchanged in the release.

The user message repeats the same contract in structured form: the `exact_enumeration`

field names the universe ("all 2^8 assignments in `feature_variables_lsb_to_msb` order") and the filter, and the `decision_rule` field states both branches. No worked example, chain of thought, or few-shot demonstration is supplied, and the schema admits no key beyond `decision` and `answer`. Three properties of this instruction matter for interpreting the panel. The algorithm is *given*, so the task is execution rather than discovery. The reasoning is required to be *silent*, so a model must carry the enumeration through one forward pass. And the contract is *identical* across the two members of every same-state pair, so a model that reads the query cannot be disadvantaged by the wording.

L The Solution, Object by Object

Figure 6 shows what a solver literally holds at each step of the same frozen pair, where Figure 5 shows how the counts collapse. Panel 1 quotes the rendered user message itself: four contiguous slices of the one 6,648-character JSON object, each tagged with the key it is taken at, so nothing downstream is introduced from outside that message. Panel 2 draws the public Boolean program as the abstract syntax tree the release seals rather than as a string, with the bit the clean-room evaluator assigns to every node; because the three dictionary facts fix every leaf, the guard is decided and exactly one branch of the program fires. Panel 3 is the version space written out cell by cell: 16 rows, one per surviving language, by the 8 declared feature bits, with the three observation-pinned columns shaded and the two queried columns inked. Panel 4 lifts each queried column out of the table and reads the scored JSON off it.

The point of the middle panel is that the paper's central claim is checkable by eye. Column `b0` is 0 in all sixteen rows, so the lexical query has one answer and the gold action is `ANSWER`; column `b4` carries eight zeros and eight ones, so the grammar query has two, and the gold action is `ABSTAIN`. Neither queried column is one of the observed columns: the constant one is fixed by the program given the facts, and the split one is never constrained at all. Every cell, identifier, count, and payload in the figure is recomputed from the sealed artifact and checked against the version-space and support certificates before the figure is allowed to draw; the queried column itself is *measured*, by toggling each feature bit over the whole declared universe and keeping the ones that move the canonical answer, rather than matched by name.

M Exact Sealed Panel Numbers

Figure 2 plots the panel; this table prints it exactly. Every value is emitted by the collector from the provenance-verified ledger, so the two cannot disagree.

N Scope and Caveats

This appendix details each point summarized in the Limitations section.

Scope of the instrument. SILICA uses small synthetic inventories and simplified grammar. It does not model language acquisition, documentation, translation quality, or typological frequency, and identifiability is exact only within each declared 128-member class drawn from a 256-language inventory—not among all plausible human analyses. The shortcut audits cover the families we specified, not every heuristic a future model might find.

The silent envelope is a confound, and we price it. The envelope is deliberately restrictive: the system message states the procedure and then requires the model to reason *silently*, the schema admits no key beyond `decision` and `answer`, and 384 new tokens are allowed. The collapse is not a truncation or formatting artifact for the four conditions at $\geq .98$ format validity, but it does measure single-pass execution, and that constraint is not innocuous. Lifting it on one checkpoint is worth $+.436$ of decision signal and $11/192$ complete route groups at 235B, and $+.030$ and $0/192$ at 1.7B. Every claim in Section 6 about the panel is therefore a claim about the silent single-pass envelope, not about what these models can do given room to derive; the trace-permitted conditions are reported as a separate stratum and never folded into the panel. The envelope explains part of the collapse and not all of it, since permission plus a $16{,}384$-token budget leaves 1.7B on the frontier, and a visible scratchpad leaves Qwen2.5-14B and 32B there too (Table 3). The decision axis in particular is computationally shallow: Appendix I shows the gold decision is a Boolean function of three printed bits with minimal formula size at most four.

Breadth of the model evidence. All four conditions that pass the format gate are Qwen2.5 checkpoints, two of which sit near a constant policy, so




Figure 5: **One item, worked end to end.** *1.* The prompt fields that carry the problem, quoted from a single user message: eight binary features, the public program C_ϕ, three dictionary facts, and the ANSWER/ABSTAIN rule. C_ϕ names no word form; it constrains only which bit vectors are real. *2.* Elimination, one square per surviving language: 256 assignments, 128 satisfying the program, then $64 \to 32 \to 16$ as each fact pins one feature bit. *3.* Readout over those same 16. The guard fires, so noun_swap_01 is constant and the lexical query is unanimous (FOX, 16/16, ANSWER); its negation never fires, so order_family stays free and splits 8/8, forcing ABSTAIN with witnesses h002 and h018 shown as explicit bit vectors. Support counts and witnesses are evaluator-only and never appear in the prompt.

the format-valid evidence comes from one model family. The trace-permitted and decoding conditions add Qwen3 and Qwen3.5 checkpoints from 0.8B to 235B, but they are exploratory controls, each varying one factor on one checkpoint, not a scaling study.

Response validity is a capability we measure, not a nuisance. Four of the eight panel conditions fall below the .95 format gate, and in the trace-permitted stratum the ability to *close* a derivation inside the budget varies from 0.0% non-termination at 235B to 28.8% at Qwen3.5-0.8B. Reporting these as excluded rows understates the point: at small scale, the constraint that binds is producing a well-formed answer at all, and no statement about identifiability can be extracted from such a condition in either direction.

The single-EOS stop contract. The local panel terminates generation at a single declared EOS identifier, which invalidates models whose turn boundary is a different token. This left the prespecified Phi-3.5 condition unevaluable; the replacement condition with a multi-token stop contract is described in Appendix F.

Two implicit conventions. The declaration binds each lexical axis to its feature bit only through matching name stems and list order, and reads identity/swapped against the declared pair order. Our prompt-only solver recovers both conventions and scores perfectly, but they are implicit, and a future release should declare the binding outright.

What the result does and does not generalize to. The registry is broad inside its phenomenon

Table 9: Sealed common-cohort panel: 1,536 rows (768 answerable, 768 underdetermined) over 192 semantic templates, one complete route each. Every value is emitted from the provenance-verified ledger; all eight conditions have request success 1.000. † marks conditions below the pre-output-frozen 0.95 format gate, reported but excluded from the hardness claim. $\langle 8 \rangle$ is the all-eight strict paired endpoint over 192 route groups. The two constant policies and the exact oracle are construction references, not competitors.

Condition	Valid	AR	FCR	AR−FCR	UR	CPA	BDA	BJA [95% CI]	$\langle 8 \rangle$
Qwen2.5-0.5B†	.423	.426	.418	+.008	.001	.471	.214	.101 [.090, .112]	.000
Qwen2.5-1.5B†	.030	.026	.034	−.008	.000	.450	.013	.006 [.003, .009]	.000
SmolLM2-1.7B†	.730	.738	.721	+.017	.000	.429	.369	.158 [.146, .170]	.000
Qwen2.5-3B	1.000	.995	.997	−.003	.003	.497	.499	.249 [.244, .253]	.000
Phi-3.5-mini†	.000	.000	.000	+.000	.000	—	.000	.000 [.000, .000]	.000
Qwen2.5-7B	1.000	1.000	1.000	+.000	.000	.497	.500	.249 [.244, .253]	.000
Qwen2.5-14B	.983	.443	.453	−.010	.531	.497	.487	.376 [.360, .391]	.000
Qwen2.5-32B	1.000	.030	.025	+.005	.975	.522	.503	.495 [.491, .499]	.000
always-`ANSWER`	1.000	1.000	1.000	+.000	.000	.500	.500	.250	.000
always-`ABSTAIN`	1.000	.000	.000	+.000	1.000	—	.500	.500	.000
exact oracle	1.000	1.000	.000	+1.000	1.000	1.000	1.000	1.000	1.000

and narrow outside it. It holds 1,536 distinct published programs over 192 templates, realising 86 distinct three-bit decision functions, and the trace-permitted escape appears in all four mechanism families ($+.354$ to $+.479$ decision signal) and across the lexical and grammar query axes (.669 versus .672 balanced strict joint accuracy). That is dense coverage of *one* query-conditioned identifiability switch in a closed, declared lexicon–grammar class. It is not evidence about open-domain underspecification, tool or API discovery, or real low-resource translation, and we make no claim about those. A resource that varied the mechanism rather than its encoding is the main thing a future version should add.

Statistical scope. Greedy decoding has no sampling variance, template-cluster intervals condition on one finite registry and omit benchmark-design uncertainty, and hardness is claimed only for complete, provenance-valid runs meeting the pre-output-frozen coverage and formatting gates.




Figure 6: **One item, object by object.** *1.* The rendered user message, quoted verbatim at each of the four keys that carry the problem. *2.* The sealed Boolean program drawn as its own syntax tree, one box per operator, each carrying the bit it evaluates to under the three facts. The guard is decided, so `noun_swap_01` is assigned and `order_family` is never touched. *3.* The 16 survivors as literal bit vectors over the 8 declared features. Shaded columns are pinned by the observations; the blue column is constant, the orange column splits 8/8, and the two narrow strips on the right give each row's canonical answer to each query. *4.* Each query lifts out its own column: one value gives FOX, 16/16, `ANSWER`; two values give `ABSTAIN` with witnesses `h002` and `h018`. The two prompts differ only in the three listed keys. Support counts and witnesses are evaluator-only and never appear in the prompt.